

BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - www.boshart.com

11-5
April 23/12

WCC SERIES BII CONDUIT WELL CAPS

ALUMINUM CONDUIT CAPS

- Heavy duty design for added durability
- Designed to provide extra clearance for pump cable
- Three stainless steel set screws for secure fit to well casing
- One stainless steel set screw to secure conduit pipe
- A well log is provided inside each cap to record installation data/specifications



PART NO.	CASING SIZE (IN)		CONDUIT PIPE SIZE	UNIT WGT - lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.				
WCC-A04	4"	4-1/2"	1"	1.25	36	15.65
WCC-A045	4-1/2"	5"	1"	1.20	30	18.43
WCC-A05	5"	5-9/16"	1"	1.40	30	19.39
WCC-A056	5-5/8"	6"	1"	1.50	30	20.27
WCC-A06	6"	6-5/8"	1"	1.75	20	21.16
WCC-A06-BLUE	6"	6-5/8"	1"	1.75	20	24.99
WCC-A066	6-5/8"	7"	1"	1.80	20	23.23
WCC-A08	8"	8-5/8"	1"	2.50	16	43.00
WCC-A10	10"	10-3/4"	1"	3.00	10	82.45



WCC-A06-BLUE
(Powder coat paint)

WCCL SERIES BII ALUMINUM LOCKING CONDUIT CAPS

- Stainless steel set screws
- Locking feature provides a secure/tamper-proof installation

PART NO.	CASING SIZE (IN)		CONDUIT PIPE SIZE	UNIT WGT - lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.				
WCCL-A06	6"	6-5/8"	1"	2.0	20	21.28



Note: Locks not included.
For illustration purposes only.

CC SERIES CAST IRON CONDUIT CAPS

- Heavy cast iron construction
- Quick installation
- Blue painted finish
- Packaged individually



PART NO.	CASING SIZE (IN)		CONDUIT PIPE SIZE	QUANTITY		CTN/CASE SHIPPING WGT - lbs	LIST PRICE-A
	I.D.	O.D.		CTN	CASE		
CC-6-CI	6, 6-1/4"	6-5/8"	1"	1	12	5/35	27.99



WCP SERIES BII PLAIN WELL CAPS

ALUMINUM PLAIN CAPS

- Heavy duty design for added durability
- Uses three stainless steel set screws for secure fit to well casing
- A well log is provided inside each cap to record installation data/specifications

PART NO.	CASING SIZE (IN)		UNIT WGT - lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.			
PC-4	4"	4-1/2"	0.87	36	23.09
PC-566 (2-STEP)	5-5/8"	UPPER 6"	1.87	21	46.59
	6"	LOWER 6-5/8"			
WCP-A06	6"	6-5/8"	1.50	24	18.89
PC-66	6-5/8"	7"	2.19	21	49.56



WCP Series



PC Series "Dicken"
(1 set screw only)

PERSONALIZED CAPS are available. Please contact your Sales Rep for further information and delivery.

BOSHART INDUSTRIES

11-6
April 23/12

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164
Fax: 1-519-595-4380 - www.boshart.com

WTC SERIES BII WATERTITE WELL CAPS - FOR STEEL OR PVC WELL CASING

- Easy to install, easy access for maintenance
- Vermin proof with large screened air vents
- Greater clearance for submersible pump cable
- Stainless steel hardware
- O-ring system ensures reliable watertight seal between well casing and retainer ring
- A second O-ring is used to seal cover and retainer ring, a positive compression seal is achieved by tightening 4 bolts
- Grounding terminal with bolt provided
- A well log is provided inside each cap to record installation data/specifications



PART NO.	CASING SIZE (IN)		CONDUIT CONNECTION	AIR VENTS	UNIT WGT - lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.					
ALUMINUM							
WTC-A04	4"	4-1/2"	1" FPT	(2) 3/4"	3.00	16	41.48
WTC-A05	5"	5-9/16"	1" FPT	(2) 3/4"	3.25	12	45.43
WTC-A06	6"	6-5/8"	1" FPT	(2) 3/4"	4.00	12	49.50
WTC-A06-BLUE	6"	6-5/8"	1" FPT	(2) 3/4"	4.00	12	56.66
WTC-A06-12	6"	6-5/8"	1-1/4" FPT	(2) 3/4"	4.00	12	50.97
WTC-A06-12-BLUE	6"	6-5/8"	1-1/4" FPT	(2) 3/4"	4.00	12	58.34
WTC-PA06 *	6"	6-5/8"	1" FPT	(2) 3/4"	2.50	12	40.32
CAST IRON - Durable Blue Powder Coat Paint							
WTC-C06	6"	6-5/8"	1" FPT	(2) 3/4"	9.5	6	57.00
WTC-C06-12	6"	6-5/8"	1-1/4" FPT	(2) 3/4"	9.5	6	58.72

8, 10 and 12" available in locking style only, see WTCL series, Page 11-8



WTC Series



WTC-A06-BLUE
(Durable Powder Coat Paint)



*WTC-PA06
(PVC cover c/w Alum. lower ring for steel casing)



WTC-C06
(Durable Powder Coat Paint)

WTC-G SERIES BII WATERTITE CAPS FOR PVC WELL CASING

- Same design as the above WTC Series but with exception that the lower ring is plastic which can be solvent welded directly to PVC well casing
- Durable UV stabilized, high impact ABS



PART NO.	CASING SIZE (IN)		CONDUIT CONNECTION	AIR VENTS	UNIT WGT - lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.					
WTC-G-P0625-06 *	6" or 6-1/4"	6-5/8" or 6.9"	1" FPT	(2) 3/4"	1.93	12	34.12
WTC-G-P0625	6-1/4"	6.90"	1" FPT	(2) 3/4"	1.75	12	29.89
WTC-G-AP0625-06 *	6" or 6-1/4"	6-5/8" or 6.9"	1" FPT	(2) 3/4"	2.93	12	42.74
WTC-G-AP0625-06-B	6" or 6-1/4"	6-5/8" or 6.9"	1" FPT	(2) 3/4"	2.93	12	46.75
WTC-G-AP0625	6-1/4"	6.90"	1" FPT	(2) 3/4"	2.75	12	38.59

* New models of well caps for 6-5/8" well casing are now available. These caps are the 6-1/4" well caps for 6.9" O.D. casing shipped with a Part No. WCCA-G0625-G06 6.9" X 6-5/8" well cap casing adapter included. The reducing adapter is not glued into the well cap so that the end user has the flexibility to use the cap for either a 6.9" O.D. or a 6-5/8" O.D. casing. This also gives the option to reduce inventories for those customers whom have both casing sizes in their territory, ensuring they never end up a job site with the wrong size well cap.



WTC-G-P0625
ABS top with
ABS glue-on
lower ring



WTC-G-AP0625
Aluminum top with
ABS glue-on lower
ring



WTC-G-P0625-06
consists of
WTC-G-P0625 well cap
plus a
WCCA-G0625-G06 ring
WTC-G-AP0625

WELL CAP CASING ADAPTER

PART NO.	SIZE	UNIT WGT-lbs	QTY CASE	LIST PRICE-A
WCCA-G0625-G06	6.9" X 6-5/8"	0.175	1	2.89

Well cap casing adapters (reducer rings) can be purchased separately if desired. If an account would prefer the option of stocking the 6-1/4" well caps for 6.9" O.D. well casing and selling the rings as a separate component. The rings are individually bagged and include installation information.



WCCA-G0625-G06 ring
glued on a 6-5/8"
casing

BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - www.boshart.com

11-7

March 21/11

WTMLC SERIES BII LOCKING WATERTITE WELL CAPS - FOR STEEL OR PVC WELL CASING

ALUMINUM WATERTITE LOCKING CAPS

- Easy to install, easy access for maintenance
- Vermin proof with large screened air vents
- Stainless steel hardware
- O-ring system to ensure reliable seal to casing
- A second O-ring is used to seal cover and retainer ring, a positive compression seal is achieved by tightening a single set screw on a specially designed tapered surface ensuring a positive seal
- Locking feature provides a secure/tamper-proof installation
- Grounding terminal with bolt provided
- A well log is provided inside each cap to record installation data/specifications



PART NO.	CASING SIZE (IN)		CONDUIT CONNECTION	AIR VENTS	UNIT WGT - lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.					
WTMLC-A04	4"	4-1/2"	1" FPT	(2) 3/4"	3.26	20	46.72
WTMLC-A04-BLUE	4"	4-1/2"	1" FPT	(2) 3/4"	3.26	20	52.90
WTMLC-A045	4-1/2"	5"	1" FPT	(2) 3/4"	3.55	16	49.66
WTMLC-A045-BLUE	4-1/2"	5"	1" FPT	(2) 3/4"	3.55	16	56.56
WTMLC-A05	5"	5-9/16"	1" FPT	(2) 3/4"	3.70	16	51.93
WTMLC-A05-BLUE	5"	5-9/16"	1" FPT	(2) 3/4"	3.70	16	58.99
WTMLC-A056	5-5/8"	6"	1" FPT	(2) 3/4"	3.92	16	54.53
WTMLC-A056-BLUE	5-5/8"	6"	1" FPT	(2) 3/4"	3.92	16	61.58
WTMLC-A06	6"	6-5/8"	1" FPT	(2) 3/4"	3.95	12	54.81
WTMLC-A06-BLUE	6"	6-5/8"	1" FPT	(2) 3/4"	3.95	12	62.81
WTMLC-A06-12	6"	6-5/8"	1-1/4" FPT	(2) 3/4"	3.95	12	55.92
WTMLC-A06-12-BLUE	6"	6-5/8"	1-1/4" FPT	(2) 3/4"	3.95	12	63.73
WTMLC-A066	6-5/8"	7"	1" FPT	(2) 3/4"	3.53	12	68.05
WTMLC-A066-BLUE	6-5/8"	7"	1" FPT	(2) 3/4"	3.53	12	73.31



Note:
Locks not included.
For illustration purposes only.

WTMLC-G SERIES BII LOCKING WATERTITE WELL CAPS - FOR STEEL OR PVC WELL CASING

LOCKING CAPS - ALUMINUM COVER WITH GLUE-ON ABS RING

PART NO.	CASING SIZE (IN)		CONDUIT CONNECTION	AIR VENTS	UNIT WGT - lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.					
WTMLC-G-AP04	4"	4.500"	1" FPT	(2) 3/4"	2.03	20	31.95
WTMLC-G-AP045	4-1/2"	4.950"	1" FPT	(2) 3/4"	2.18	16	34.74
WTMLC-G-AP05	5"	5.563"	1" FPT	(2) 3/4"	2.36	16	36.90
WTMLC-G-AP0625-06 *	6" or 6-1/4"	6-5/8" or 6.9"	1" FPT	(2) 3/4"	2.58	12	40.56
WTMLC-G-AP0625	6-1/4"	6.900"	1" FPT	(2) 3/4"	2.40	12	39.02

* A well cap for 6-5/8" well casing is now available. These caps are the 6-1/4" well caps for 6.9" O.D. casing shipped with a Part No. WCCA-G0625-G06 6.9" X 6-5/8" well cap casing adapter included. The reducing adapter is not glued into the well cap so that the end user has the flexibility to use the cap for either a 6.9" O.D. or a 6-5/8" O.D. casing. This also gives the option to reduce inventories for those customers whom have both casing sizes in their territory, ensuring they never end up a job site with the wrong size well cap.



WTMLC-G-AP0625-06 consists of WTMLC-G-AP0625 well cap plus a WCCA-G0625-G06 ring

WELL CAP CASING ADAPTER

PART NO	SIZE	UNIT WGT-lbs	QTY CASE	LIST PRICE-A
WCCA-G0625-G06	6.9" X 6-5/8"	0.175	1	2.89

Well cap casing adapters (reducer rings) can be purchased separately if desired. If an account would prefer the option of stocking the 6-1/4" well caps for 6.9" O.D. well casing and selling the rings as a separate component. The rings are individually bagged and include installation information.



WCCA-G0625-G06 ring glued on a 6-5/8" casing

BOSHART INDUSTRIES

11-8
April 23/12

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164
Fax: 1-519-595-4380 - www.boshart.com

WTCC SERIES WATERTITE LOCKING CAPS - CAST IRON

- Rugged cast iron construction with durable blue powder coat paint finish
- Vermin Proof design c/w two large stainless steel screened vents
- Locking feature provides a secure / tamper proof installation
- Wide gasket provides a positive compression seal between the well casing and cap as well as the cap cover and retainer ring, compression is achieved by tightening 5 bolts
- Deep, forgiving pocket designed for sealing unevenly cut casing - gasket will seal as far as 1-1/2" from the top of the casing
- Increased clearance for the pump cable



PART NO.	CASING SIZE (IN)		CONDUIT CONNECTION	AIR VENTS	UNIT WGT - lbs	QUANTITY		LIST PRICE-A
	I.D.	O.D.				CTN	CASE	
WTCC-5-CI	5"	5-9/16"	1" FPT	(2) 3/4"	9.85	1	6	63.86
WTCC-6-CI	6" , 6-1/4"	6-5/8"	1" FPT	(1) 1/2"	10.5	1	6	68.80
WTCC-6-CI-12	6" , 6-1/4"	6-5/8"	1-1/4" FPT	(1) 1/2"	10.5	1	6	70.86
WTCC-66-CI	6-5/8"	7"	1-1/4" FPT	(2) 3/4"	11.18	1	6	81.55



8" , 10" , 12" WTCL SERIES BII WATERTITE LOCKING WELL CAPS

ALUMINUM WATERTITE LOCKING CAPS

- Easy to install, easy access for maintenance
- Vermin proof with large screened air vents
- Stainless steel hardware
- O-ring system to ensure reliable seal to casing
- A second O-ring is used to seal cover and retainer ring, a positive compression seal is achieved by tightening 6 bolts
- Locking feature provides a secure/tamper-proof installation
- Grounding terminal with bolt provided
- A well log is provided inside each cap to record installation data/specifications



Note:
Locks not included.
For illustration purposes only.

PART NO.	CASING SIZE (IN)		CONDUIT CONNECTION	AIR VENTS	UNIT WGT - lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.					
WTCL-A08	8"	8-5/8"	1-1/4" FPT	(2) 3/4"	5.25	8	101.90
WTCL-A10	10"	10-3/4"	1-1/4" FPT	(2) 3/4"	6.00	5	214.00
WTCL-A12	12"	12-3/4"	1-1/4" FPT	(2) 3/4"	6.50	5	275.91

