

SUMP PUMPS

B75-M1/B75-V1


Oil-filled motor with automatic reset overload provides safe operation

Typical Application	Basement sumps, dewatering, utility
Capacities	100 GPM (6.3 LPS)
Heads	25 ft. (7.6 m)
Operation	Automatic or manual
Solids Handling	1/8" (3.2 mm)
Liquids Handling	Drain water
Continuous Liquid Temp.	77°F (25°C)
Motor Electrical Data	3/4 HP (3450 RPM); PSC with thermal overload protection, 115V, 7.5 FLA, 1Ø, 60Hz
Acceptable pH Range	6-9
Shaft Seal	Double lip
Housing	Resin and stainless steel
Power Cord	10' (3 m) or 20' (6 m), 16/3, STJW, STJW-A
Discharge	1-1/4" or 1-1/2" with adapter
Min. Sump Diameter	Wide Angle = 14" (345 mm) Vertical = 10" (254 mm)



Superior Features

- 3/4 HP
- Energy-efficient PSC motor
- Includes check valve and universal adapter for 1-1/4" (32 mm) or 1-1/2" (38.1 mm) pipe
- High-impact resin and stainless steel construction
- Piggyback-style float for automatic or manual operation
- Ball-bearing construction for long life
- Easily replaceable power cord with optional lengths available



Piggyback Switch Plug

Performance

