

MODEL: S3WR — Recessed Impeller Sewage Pump

R.P.M.	1750
MOTOR TYPE	ENCLOSED, OIL COOLED INDUCTION, VFD SUITABLE
MOTOR DESIGN NEMA TYPE	B (3Ø) L (1Ø)
GENERAL INSULATION CLASS	B
STATOR WINDING CLASS	B
MAXIMUM STATOR TEMPERATURE	260°F (130°C)
VOLTAGE TOLERANCE	±10%

HP	VOLTAGE	PHASE	HERTZ	NEC CODE	START AMPS	RUN AMPS	RUN KW	START KVA
1.5	208	1	60	A	39.9	16.6	2.7	8.3
	230				33.4	15	2.3	7.7
1.5	208	3	60	F	45	11	2.2	16.2
	230			H	48	10		19.1
	460			H	24	5		19.1
	575			H	19	4		18.9
2	208	1	60	A	39.9	17.7	3.4	8.3
	230				33.4	16	3	7.7
2	208	3	60	F	45	13	2.9	16.2
	230			H	48	12		19.1
	460			H	24	6		19.1
	575			H	19	4.8		18.9
3	230	1	60	A	33.4	20	3.8	7.7
3	208	3	60	F	45	15	3.5	16.2
	230			H	48	13.5		19.1
	460			H	24	6.8		19.1
	575			H	19	5.5		18.9