
EZ SERIES® SINGLE PHASE SIMPLEX

Single Phase, Simplex Demand Dose or Timed Dose Float Controlled System for Pump Control and System Monitoring



The EZ Series® simplex control panel is designed to control one 120, 208, 240 VAC single phase pump in water and sewage installations.

The EZ Series® simplex control panel features a backlit LCD display on the inside of the front cover for programming and system monitoring, including: float status, elapsed time pump run, cycle counter, alarm counts (high water/power fail), float error count, auxiliary alarm counter, timer override count (TD only).

The panel configuration can be easily converted in the field to either a timed dose or demand dose.

Optional mounting post has removable access door for easy wiring. The post can be mounted in the ground directly, over a 4x4, or conduit. This panel is available with optional duo alarm for local code compliance; and optional EZconnex® float connection system.

COMPONENTS

- Enclosure base measures 10 x 8 x 6 inches (25.4 x 20.32 x 15.24 cm); NEMA 4X enclosure (ultraviolet stabilized thermoplastic with removable mounting feet for outdoor or indoor use) includes locking latch as standard
- 2. Red alarm beacon provides visual check of alarm condition
- 3. Exterior Alarm Test/Silence switch allows horn and light to be tested and horn to be silenced in an alarm condition; alarm automatically resets once alarm condition is cleared
- Two circuit breakers: one for pump power; another for control and alarm power
- 5. Power relay controls pump by switching electrical lines
- 6. Float connection terminal block with auxiliary alarm contact
- 7. Incoming control/alarm power & pump power terminal block
- 8. Control Power indicator light
- 9. Alarm Power indicator light
- 10. Pump Run indicator light
- 11. Simplex controller (touch safe housing) for pump control:
 - Backlit LCD display shows system information including: pump elapsed time (hh:mm), pump events (cycles), and alarm condition (counts)
 - b. Menu/Enter button used for viewing panel settings
 - c. Set/Change button used for programming panel settings
 - d. Pump Push To Run momentary switch pump activates when pressed
 - e. Control and Alarm Power shorted condition indicators
- Alarm horn provides audio warning of alarm condition (83 to 85 decibel rating - located inside panel on cover, not shown)

Note: Options, voltage, and amp range selected may change enclosure size and component layout.

Note: Schematic/Wiring Diagram and Pump Specification Label are located inside the panel.









EZS			1 W	4	3A6A8AC10E15A
	ODEL YPE			JMP FLOAT SWITCH APPLICATION	OPTIONS (LISTED BELOW)
CONTROL PANEL	1	EZS			
MODEL TYPE		1	Simplex Timed Dose (includes Options 3A6A8AC10E15A as stand	dard)	EZS Simplex Base Price
WIODELTIFE		2	Simplex Demand Dose (includes Option 3A6A8AC10E15A as star	ndard)	
ALARM PACKAGE ✓		1	Alarm Package (includes test/silence switch, fuse, red light, & horn	n)	Alarm Package
ENCLOSURE RATING 🗸		W	Weatherproof, NEMA 4X (engineered thermoplastic)		
STARTING DEVICE		1	120/208/240V		Enclosure Rating
STARTING DEVICE		9	120V only	;	
PUMP FULL		0	0 - 7 FLA		Starting Device
LOAD AMPS		1	7 - 15 FLA	j	
LOAD AIIII O		2	15 - 20 FLA	e) Sun 1 above)	Pump Full Load Amps
PUMP	/	4	Circuit Breaker(s) 120V (select STARTING DEVICE Option 9 above		
DISCONNECTS	_	4	Circuit Breaker(s) 120/208/240V (select STARTING DEVICE Optio	Pump Disconnects	
		Н	Floats - Pump Down (select Option 17 below) Timed dose = timer enable and alarm / Demand dose = stop, start,		Float Switch Application
FLOAT SWITCH APPLICATION		Е	EZconnex® Float Switch System (select Option 33, 35 or 36 below)	Timed Dose Demand Dose	Total Options
		Х	No Floats	Timed Dose Demand Dose	TOTAL LIST PRICE

	OPTIONS	DESCRIPTION		OPTIONS	DESCRIPTION
	1J	Duo Alarm Inputs		18A	Timer Override Float (Timed Dose Float Panel Only)
1	3A	Alarm Flasher (Included as standard)		22G	2 1/2" Hub Installed with 6 Hole Cord Seal
	4A	Redundant Off (Timed Dose Float Panel Only) (must also select Option 4D if floats are required)		33D 	EZconnex® 3-Port, 25', with 10' Floats (3) / Pipe Clamp
	44			33E	EZconnex® 3-Port, 50', with 10' Floats (3) / Pipe Clamp
	4D	Redundant Off Float (must also select Option 4A and Option 17)		33G	EZconnex® 3-Port, 25', with 20' Floats (3) / Pipe Clamp
1	6A	Auxiliary Alarm Contact, Form A (Included as standard)		33H	EZconnex® 3-Port, 50', with 20' Floats (3) / Pipe Clamp
1	8AC	Display Board - Includes: ETM Counter, Events (Cycles) Counter, Alarm Counter (included as standard)		35D ■	EZconnex® 4-Port, 25', with 10' Floats (4) / Pipe Clamp (Timed Dose Only)
1	10E	Lockable Latch - NEMA 4X (included as standard)		055	EZconnex® 4-Port, 50', with 10' Floats (4) / Pipe Clamp (Timed Dose Only)
	10P	Mounting Post (Factory installed with 2.5" cord seal)		35E	
1	15A	Control/Alarm Circuit Breaker (Included as standard)		250	EZconnex® 4-Port, 25', with 20' Floats (4) / Pipe Clamp (Timed Dose Only)
	16A	10' Cord in Lieu of 20' Cord (per Float)		35G	
	16B	15' Cord in Lieu of 20' Cord (per Float)		2511	EZconnex® 4-Port, 50', with 20' Floats (4) / Pipe Clamp (Timed Dose Only)
	16C	30' Cord in Lieu of 20' Cord (per Float)		35H ■	
	16D	40' Cord in Lieu of 20' Cord (per Float)		36D	EZconnex® 3-Port, 25', with 10' Floats (2) / Pipe Clamp, Sealing Plug
	17C	Sensor Float® / Internally Weighted (per Float) - Mercury		36E	EZconnex® 3-Port, 50', with 10' Floats (2) / Pipe Clamp, Sealing Plug
	17D	Sensor Float® / Externally Weighted (per Float) - Mercury		36G	EZconnex® 3-Port, 25', with 20' Floats (2) / Pipe Clamp, Sealing Plug
	17G	SJE MilliAmpMaster™ / Pipe Clamp (per Float) - Mechanical		36H	EZconnex® 3-Port, 50', with 20' Floats (2) / Pipe Clamp, Sealing Plug
	17H	SJE MilliAmpMaster™ / Externally Weighted (per Float) - Mechanical			
	17J	Sensor Float® / Pipe Clamp (per Float) - Mercury			

■ EZconnex® mechanically-activated, narrow angle float switches with quick release connections

Part #	Pre-configured Panels for Easy Ordering				
1030771	EZS21W114X3A6A8AC10E15A				
1052607	EZS11W114H3A6A8AC10E15A17G				