

# TANK ALERT® XT ALARM SYSTEM

Versatile, Indoor or Outdoor Liquid Level Alarm System

This alarm system monitors liquid levels in lift pump chambers, sump pump basins, holding tanks, sewage, agricultural, and other water applications.

The Tank Alert® XT indoor/outdoor alarm can serve as a high or low level alarm depending on the float switch model used.

The alarm horn sounds and the red LED beacon illuminates when a potentially threatening liquid level condition occurs. The horn can be silenced, but the alarm light remains on until the condition is remedied. Once the condition is cleared, the alarm will automatically reset.

A "power on" light on the switch indicates power to the alarm panel.

## FEATURES

- Enclosure meets Type 3R water-tight standard
- Automatic alarm reset, horn silence switch, and alarm test switch
- Alarm horn sounds at 85 decibels at 10 feet (3 meters)
- Alarm system (when installed on separate circuit) operates even if pump circuit fails

## OPTIONS

When ordered with the alarm, the system is available with:

- Alternate float switch models for high or low liquid level warning
- Auxiliary dry normally open contacts for easy attachment of remote devices
- Premounted terminal block so enclosure can also be used as a junction box for splicing pump, pump switch, and pump power; meets NEC standard for junction boxes
- 6 foot (1.8 meter) power cord and liquid-tight connectors



SIGNALING  
TYPE E  
UL  
LISTED  
288X

SP  
LR54245

5  
YEAR  
WARRANTY



## TANK ALERT® XT - Versatile, indoor or outdoor liquid level alarm system.

Part #	Description (120V)	Shipping Weight
1009923*	TAXT-01H (120 VAC w/15' SJE SignalMaster® High Level)	3.00 lbs.
1010251	TAXT-01L (120 VAC w/15' SJE SignalMaster® Low Level)	3.00 lbs.
1004442	TAXT-01H (120 VAC w/15' Sensor Float® High Level)	3.00 lbs.
1005140	TAXT-01L (120 VAC w/15' Sensor Float® Low Level)	3.00 lbs.
1005141	TAXT-01X (120 VAC no float)	1.50 lbs.
Part #	Description (120V with Terminal Block)	Shipping Weight
1012416	TAXT-01HAUXTB (120 VAC w/15' SJE SignalMaster® High Level Aux Con TB)	3.50 lbs.
1022241	TAXT-01HTB (120 VAC w/15' SJE SignalMaster® High Level TB)	3.50 lbs.
1005481	TAXT-01HTB (120 VAC w/15' Sensor Float® High Level TB)	3.50 lbs.
1005835	TAXT-01LTB (120 VAC w/15' Sensor Float® Low Level TB)	3.50 lbs.
1005836	TAXT-01XTB (120 VAC no float TB)	2.00 lbs.
1009214	TAXT-01HAUXTB (120 VAC w/15' SJE Sensor Float® High Level Aux Con TB)	3.50 lbs.
Part #	Description (120V with Options)	Shipping Weight
1006850	TAXT-01HAUX (120 VAC w/15' Sensor Float® High Level Auxiliary Contacts)	3.50 lbs.
1006690	TAXT-01HPC (120 VAC w/15' Sensor Float® High Level Power Cord)	3.50 lbs.
1032257	TAXT-01HAUX (120VAC w/ 15' SJE SignalMaster® High Level Auxiliary Contacts)	3.1 lbs.
1057473	TAXT-01HPC (120 VAC w/15' SJE SignalMaster® High Level Power Cord)	3.3 lbs.
OPTION AUX	Auxiliary contacts (factory installed option only)	N/A
OPTION PC	6' power cord with two RCC8 1/2" liquid-tight connectors	N/A

\*This item is an SJE Rhombus Quick Ship product which normally ships within 1 business day from receipt of order at no additional charge.

**H** = High Level **L** = Low Level **X** = No Float **TB** = Includes Terminal Block **PC** = Power Cord **AUX** = Auxiliary Contacts

**MASTER CARTON holds 12 boxed units.**

### CONTROL SWITCH OPTIONS

The Tank Alert® XT alarm system comes standard with a 15 foot SJE SignalMaster® control switch with mounting clamp. Other float switches are available. See control switch section of the catalog. To determine the price of alarm with an alternate float, add the price of the part number with "no float" to the price of the float switch.

### SPECIFICATIONS

**VOLTAGE:** 120 VAC, 50/60 Hz

**ALARM ENCLOSURE:** 6.5 x 4.5 x 3 inches (16.51 x 11.43 x 7.62 cm), indoor/outdoor, weatherproof, thermoplastic, meets Type 3R water-tight standard

**ALARM HORN:** 85 decibels at 10 feet (3 meters), meets Type 3R water-tight standard as installed by factory

**ALARM BEACON:** UL Listed, Type 4X beacon assembly

**TEST/SILENCE SWITCH:** certified to IP66 and IP68 standards

**AUXILIARY ALARM CONTACTS (OPTIONAL):** 120 VAC, 5 amps max., 50/60 HZ

**PRE-MOUNTED TERMINAL BLOCK (OPTIONAL):** 20 amps, 120/230 VAC

**POWER CORD:** (optional) 6 foot (1.8 meters) cord with 120 VAC plug and two RCC8 1/2 inch liquid-tight connectors

**FLOAT SWITCH:** SJE SignalMaster® control switch with mounting clamp

**CABLE:** 15 feet (4.57 meters), flexible 18 gauge, 2 conductor (UL) SJOW, water-resistant (CPE)

**FLOAT:** 2.74 inch diameter x 4.83 inch long (7 cm x 12.3 cm), high impact, corrosion resistant polypropylene housing for use in sewage and non-potable water up to 140°F (60°C)

**MAXIMUM WATER DEPTH:** 30 feet (9 meters), 13 psi

**ELECTRICAL:** 5 amps, 125 VAC/250 VAC, 50/60 Hz