SUBMITTAL DATA SHEET


Sump, Sewage, & Effluent Pumps DuraMAC™ | Guardian


5050CTSJ15, 5050CVSJ15 & 5050CTSJH25 1/2 HP High Volume Sewage Pump




This high quality and dependable pump features a stainless steel housing and a cast iron base. With a built-in thermal overload protection for safety and a permanent split capacitor continuous duty motor. Convenient carrying handle is attached.

Performance Curve







Performance

Model	Gallons per Minute in Feet									
5050CTSJ15 5050CVSJ15 5050CTSJH25	0	5	10	15	20	25	30			
	140	123	97	72	49	25	3			

Specifications

Model						Discharge	Cord	Solids			
No.	HP	Volts	Hz	Amps	Construction	Size	Length	Handling	Switch	Phase	Wt.
5050CTSJ15	1/2	120	60	12	Cast Iron / Stainless Steel	2"	15'	2"	Tethered	1	25
5050CVSJ15	1/2	120	60	12	Cast Iron / Stainless Steel	2"	15'	2"	Vertical	1	25
5050CTSJH25	1/2	120	60	12	Cast Iron / Stainless Steel	2"	25'	2"	Vertical	1	25

SUBMITTAL INFORMATION

- Split Capacitor Motor -
- 1/2 HP continuous duty, thermal protected
- Lifts water up to 30' of vertical height
- 15' power cord & 25' option

- Large 2" discharge for high capacity pumping
- Easily handles 2" solids
- Non-clogging stainless steel vortex impeller
- Vertical, tethered, or no float switch



NO-LEAD: The weighted average of the wetted surface of this no-lead product contacted by consumable water contains less than one quarter of one percent (0.25%) lead.



A.Y. McDonald Mfg. Co.

P.O. Box 508

Dubuque, IA 52004-0508

Toll Free: 1-800-292-2737 Fax: 1-800-832-9296

Hours: 7:00 a.m. - 5:00 p.m., CST

sales@aymcdonald.com www.aymcdonald.com

A.Y. McDonald considers the information on this assembly drawing correct when published. Item and option availability, including specifications, are subject to change without notice.