

Adapters - Flanges

101 Casing Adapter

For all 8200, 8600 and 1500 Series. With tapped openings for offset installations using two pipes to the jet pump and single pipe jet ejector in the well. Slips onto the well casing and is secured by tightening the two bolts and nuts (one pictured). Also allows the pump to bolt directly to the well head using the specially designed fiber gasket between the two flat faces.



Part No.	Wt.
6450-103	9

106 Casing Adapter

For all single pipe 1000 Series. Slips onto the well casing and is secured by tightening the two bolts and nuts (one pictured). Thick rubber compression gasket eliminates threading or welding of casing. 1 1/4" x 1" face bushing or reducing nipple required to permit use of 1" drop pipe. Adapters and flanges bolt directly to the base of all 1000 and 1000SW Series pumps and 8200, 8600, and 1500 series. Sizes Available: 2"



Part No.	Wt.
6450-110	9

108 Threaded Flange

For all 1000 Series. Tapped openings permit use directly over standard 4" well seal as well as offset installation of all 1000 and 1000SW Series pumps. Furnished with all 1000SW pumps. Sizes Available: 4" | Includes 1" and 1 1/4" NPT



Part No.	Wt.
6421-124	3

100-4 Casing Adapter Plate

For use with 1000 series, not threaded with 1 1/2" & 1 1/2" opening.

Part No.	Wt.
6316-114	1.4



Flange Gasket

For use with 100-4, 106, & 108

Part No.	Wt.
6316-257	.1

Pressure Switches see page.