

Horizontal Split Case Centrifugal Pumps

Pump Size	Model No	Size Code	STANDARD CONSTRUCTION		OPTIONAL for PSI (2)		
			Cast Iron Flange Rating PSI (1)		Maximum Casing Working Pressure PSI	Flange Rating and Casing Working Pressure PSI	Casing Material Bronze Fitted or All Iron
			Suction	Discharge			
2 x 1-1/2 x 8	5061	1615	125	125	175	250	D.I.
3 x 2 x 8	5061	2215	125	125	175	250	D.I.
3 x 2 x 11	5061	2235	125	125	175	250	C.I.
3 x 2 x 14	5061	2255	125	125	175	250	D.I.
3 x 2 x 14B	5061	2256	125	125	175	250	D.I.
4 x 3 x 9	5061	3125	125	125	175	250	D.I.
4 x 3 x 11	5062	3135	125	125	175	250	C.I.
4 x 3 x 14	5062	3155	125	125	175	250	D.I.
4 x 3 x 17	5062	3175	125	125	175	250	D.I.
6 x 4 x 9A	5062	4223	125	125	175	250	D.I.
6 x 4 x 9	5062	4225	125	125	175	250	D.I.
6 x 4 x 12	5062	4245	125	125	175	250	D.I.
6 x 4 x 14-1/2	5062	4265	125	125	175	250	D.I.
6 x 4 x 17	5063	4275	125	125	175	250	D.I.
8 x 6 x 9	5062	6125	125	125	175	250	D.I.
8 x 6 x 12A	5063	6142	125	125	175	250	D.I.
8 x 6 x 12	5063	6145	125	125	175	250	D.I.
8 x 6 x 14-1/2	5063	6165	125	125	175	250	D.I.
8 x 6 x 17	5063	6178	125	125	175	250	D.I.
8 x 6 x 20	5064	6185	125	250	215	250	D.I.
10 x 8 x 12	5063	8145	125	125	175	250	D.I.
10 x 8 x 14-1/2	5063	8165	125	125	175	250	D.I.
10 x 8 x 17A	5064	8172	125	125	175	250	D.I.
10 x 8 x 17	5064	8175	125	125	175	250	D.I.
10 x 8 x 20	5064	8185	125	250	215	250	D.I.
12 x 10 x 12	5064	7145	125	125	175	250	D.I.
12 x 10 x 14-1/2	5064	7165	125	125	150	250	D.I.
12 x 10 x 17	5064	7175	125	125	175	250	D.I.
14 x 12 x 14-1/2	5064	7565	125	125	175	---	---
14 x 12 x 14-1/2	5064L	7566	125	125	175	---	---

(1) On Model 5060 Series pumps, all standard 125 psi flanges have 250 psi thickness with 125 psi O.D. and drilling

(2) With Optional Construction for 250 psi, the hydrostatic test pressure is 375 psi.

(3) Maximum suction pressure is equal to maximum working pressure minus total head.

Temperature Limitations: Pumps with Packed Stuffing Box - 250°F maximum
Pumps with Mechanical seals - See Price Pages

C.I. = Cast Iron
D.I. = Ductile Iron