Standard Materials of Construction - Fig. 5260

Packed Stuffing Box & Water Jacketed Bearings Bulletin 5260



Two Stage Split Case Centrifugal Pumps

| ITEM NO. | NAME OF PART | STANDARD FITTED | ALL IRON |
|-------------|---|--------------------|--------------------|
| 1A | Casing (Lower Half) | Cast Iron | Cast Iron |
| 1B | Casing (Upper Half) | Cast Iron | Cast Iron |
| 2A | Impeller (1st Stage) | Bronze | Cast Iron |
| 2B | Impeller (2nd Stage) | Bronze | Cast Iron |
| 6 | Shaft | 12L14 | 12L14 |
| 7 | Casing Ring | Bronze | Cast Iron |
| 8 | Impeller Ring | Bronze | Steel |
| 13 | Packing | Graphite - Polymer | Graphite - Polymer |
| 14 | Shaft Sleeve | Stainless | Stainless |
| 16 | Bearing (Inboard) | Steel | Steel |
| 17 | Stuffing Box Gland | Bronze | Cast Iron |
| 18 | Bearing (Outboard) | Steel | Steel |
| 20 | Shaft Sleeve Nut | Bronze | Steel |
| 29 | Seal Cage | Bronze | Cast Iron |
| 31 | Water Jacketed Bearing Housing (Inboard) | Cast Iron | Cast Iron |
| 32 | Impeller Key | Stainless | Stainless |
| 33 | Water Jacketed Bearing Housing (Outboard) | Cast Iron | Cast Iron |
| 38 | Shaft Sleeve Gasket | Vellumoid | Vellumoid |
| 40 | Deflector (Liquid) | Neoprene | Neoprene |
| 41 | Bearing Cap (Inboard) | Cast Iron | Cast Iron |
| 43 | Bearing Cap (Outboard) | Cast Iron | Cast Iron |
| 72 | Thrust Collar | Steel | Steel |
| 73 | Casing Gasket - Suction Side | Cork - Cellulose | Cork - Cellulose |
| 73A | Casing Gasket - Discharge Side | Cork - Cellulose | Cork - Cellulose |
| 109 | Interstage Diaphragm | Bronze | Cast Iron |
| 127A | Seal Piping | Copper | Steel |
| 192 | Retaining Ring (Bearing) | Steel | Steel |
| 193 | Adapter Base | Steel | Steel |



WARNING:

CANCER AND REPRODUCTIVE HARM - WWW.P65WARNINGS.CA.GOV

SECTION 30 PAGE 8 DATE 10/18

