


Sizes 1-1/4" / 32 mm **Direct Acting Pump Control**

LOW-LEAD



Materials



Item #	Qty	Description	Material	Item #	Qty	Description	Material	
1	1	Adjusting Screw	Steel	12	12 1 Diaphragm		Nitrile/Nylon	
2	1	Spacer	ABS	14 1 Friction Ring		Brass C36000		
3	2	Jam Nut	Steel	16	1	Stem	Stainless Steel 304	
4	1	Cover	Noryl	17	1	O-Ring	Buna-n	
5	1	Spring Button	Steel	18	1	Cartridge	Delrin	
6	1	Spring	Steel	22 1 Screw		Stainless Steel 18-8		
7	1	HHCS	Stainless Steel 18-8	24	1	Body	Bronze C89833	
8	1	Diaphragm Plate	Steel	25	2	Union Disc	EPDM	
9	1	Tooth Lock Washer	Steel	26	2	Union Nut	Bronze C31400	
10	1	O'Ring	Buna-n	27	2	Union	Bronze C31400	
11	1	O'Ring	Buna-n	28	1	Disc (Slotted)	Stainless Steel 303	

Part Number C152002E 15-75 psi Part Number C152102E 15-150 psi

Dimensions

Max Temp: 180°F (82°C) Max Inlet Pressure 400psi (27bar)

Siz	ze	Part #	A		В		С		Weight	
inch	mm		inch	mm	inch	mm	inch	mm	lbs	kg
1-1/4	32	C152002E	8-3/8	213	5	127	7-3/8	187	5.3	2.4

Flomatic Corporation can accept no responsibility for possible errors in catalogues, brochures and other printed material. Flomatic Corporation reserves the right to alter its products without notices. This also applies to product already agreed. All trademarks in this material are property of the respective companies. All right reserved. ©2011 Flomatic Corporation. The drawings & information on this drawing sheet are the sole & exclusive property of Flomatic Corporation. Any reproduction, distribution, display or use of these drawingsor information in whole or in part without written authorization of Flomatic Corporation is strictly prohibited.

