

## HIGH PERFORMANCE BOOSTER PUMPS - BT4 SERIES 56C PUMP ENDS

### FEATURES

- 56C standard motor bracket for use with any customer-supplied motor
- All stainless steel construction, including a stainless steel bracket with a rugged support foot for horizontal or vertical mounting and a handle for portability
- Built with Franklin's patented (U.S. patent) 7,290,984 Tri-Seal floating stage system, providing maximum efficiency, longevity, and performance
- Acetal impellers, Modified PPO diffusers, and 300-series stainless steel hub, eye seals, shaft, and shell
- Mechanical seal with standard phenolic/ceramic faces, FKM elastomers, and stainless steel components
- Shut-off pressures up to 270 psi, flow rates from 5-25 gpm



### ORDERING INFORMATION

Model	HP	Suc. x Dis. (NPT)	GPM	Order No.	Wt. (lbs)
5BT03S4-PE	1/3	1" x 1"	5	95920507	18
5BT05S4-PE	1/2			95920509	19
5BT07S4-PE	3/4			95920512	20
5BT1S4-PE	1			95920515	21
7BT05S4-PE	1/2		95920708	7	18
7BT07S4-PE	3/4		95920710	19	
7BT1S4-PE	1		95920714	20	
7BT15S4-PE	1-1/2		95920719	24	
10BT05S4-PE	1/2		95921007	10	18
10BT07S4-PE	3/4		95921008	19	
10BT1S4-PE	1		95921011	20	
10BT15S4-PE	1-1/2		95921015	23	
10BT2S4-PE	2		95921018	24	
15BT07S4-PE	3/4		95921506	15	18
15BT1S4-PE	1		95921508	19	
15BT15S4-PE	1-1/2		95921512	20	
15BT2S4-PE	2		95921515	23	
20BT07S4-PE	3/4		95922005	20	18
20BT1S4-PE	1		95922007	19	
20BT15S4-PE	1-1/2		95922010	20	
20BT2S4-PE	2		95922012	23	
20BT3S4-PE	3		95922015	24	
25BT1S4-PE	1		95922506	25	18
25BT15S4-PE	1-1/2		95922508	19	
25BT2S4-PE	2		95922510	20	
25BT3S4-PE	3		95922513	24	