

# Electrical Data – S4NRC/S4NVX

## MODEL: S4NRC & S4NVX – Recessed Impeller Sewage Pump

R.P.M.	1750			
MOTOR TYPE	ENCLOSED, OIL COOLED INDUCTION, VFD SUITABLE			
MOTOR DESIGN NEMA TYPE	B(3Ø) L(1Ø)			
GENERAL INSULATION CLASS	F			
STATOR WINDING CLASS	F			
MAXIMUM STATOR TEMPERATURE	311°F (155°C)			
MOTOR PROTECTION	BI-METALLIC, TEMPERATURE SENSITIVE DISC, SIZED TO OPEN AT 120°C AND AUTOMATICALLY RESET @ 90-65°C DIFFERENTIAL, ONE IN SINGLE PHASE, TWO IN THREE PHASE			
ELECTRICAL RATINGS	HEAT SENSOR	24VDC 5AMPS	115VAC 5AMPS	230VAC 5AMPS
	SEAL FAIL	300VAC 5mA		
VOLTAGE TOLERANCE	±10%			

HP	VOLTAGE	PHASE	MEC CODE	SF	FULL LOAD AMPS	SF AMPS	LOCKED ROTOR AMPS	RUN KW	START KVA	RUN KVA	MTR. EFF. @ SF	MTR. EFF. 100% FL	MTR. EFF. 75% FL	MTR. EFF. 50% FL	PWR. FACT. @ SF	PWR. FACT. 100% FL	PWR. FACT. 75% FL	PWR. FACT. 50% FL
3	230	1	G	1.2	17.1	20.0	79.0	3.3	18.2	3.9	.67	.67	.65	.57	.88	.85	.80	.71
3	200	3	J	1.2	10.9	12.8	64.5	3.1	22.3	3.8	.73	.72	.70	.64	.83	.82	.80	.72
	230				9.5	11.1	56.0											
	460				4.8	5.6	28.0											
	575				3.8	4.5	22.5											
5	230	1	G	1.2	29.5	34.2	125	5.7	28.8	6.8	.66	.66	.65	.60	.87	.84	.77	.64
5	200	3	J	1.2	17.6	20.6	108	4.8	37.4	6.1	.79	.79	.77	.72	.80	.78	.73	.62
	230				15.3	17.9	94.0											
	460				7.6	8.9	47.0											
	575				6.1	7.2	37.6											
7½	200	3	K	1.2	29.0	32.9	194	7.2	67.0	10.1	.78	.78	.76	.71	.76	.72	.66	.56
	230				25.2	28.6	168											
	460				12.6	14.3	84											
	575				10.1	11.4	67.2											