

MODEL: S3WR — Recessed Impeller Sewage Pump

R.P.M.	3450
MOTOR TYPE	ENCLOSED, OIL COOLED INDUCTION, VFD SUITABLE
MOTOR DESIGN NEMA TYPE	B (3Ø) L (1Ø)
GENERAL INSULATION CLASS	B
STATOR WINDING CLASS	B
MAXIMUM STATOR TEMPERATURE	260°F (130°C)
VOLTAGE TOLERANCE	±10%

HP	VOLTAGE	PHASE	HERTZ	NEC CODE	START AMPS	RUN AMPS	RUN KW	START KVA	
1.5	208	1	60	F	39.9	14.8	3.3	8.3	
	230				33.4	12.8		7.7	
1.5	208	3	60	J	30	2.7	2.7	10.8	
	230			K	32			8	12.8
	460			K	16			4	12.8
	575			K	13			3.2	13.0
2	208	1	60	D	63	3.5	3.5	13.1	
	230			E	63			16	14.5
2	208	3	60	H	53	3.4	3.4	19.1	
	230				50			12	19.9
	460				25			6	19.9
	575				20			4.8	19.9
3	230	1	60	E	63	19	4.3	14.5	
3	208	3	60	H	53	4.2	4.2	19.1	
	230				50			13.3	19.9
	460				25			6.7	19.9
	575				20			5.2	19.9