

MODEL: H4H(X) — Solids Handling Sewage Pumps

Physical Data:

DISCHARGE SIZE	4" 125# ANSI
IMPELLER TYPE	BALANCED, ENCLOSED, MONO-VANE
CABLE LENGTH	35' STANDARD 50' OPTIONAL

Liquid Handling:

SOLIDS SIZE	3" SPHERICAL
MAXIMUM LIQUID TEMP.	140°F
ACCEPTABLE PH RANGE	6 - 9
SPECIFIC GRAVITY	0.9 - 1.1
VISCOSITY	28 - 35 SSU

Temperature:

MAXIMUM STATOR	356°F
OIL FLASH POINT	390°F
HEAT SENSOR	Open: 257°F MAX./239°F MIN. Closed: 194°F MAX./119°F MIN.

Technical Data:

POWER CORD TYPE	SOOW, W				
SENSOR CORD TYPE	SOOW				
MATERIALS OF CONSTRUCTION	MOTOR HOUSING	CAST IRON	ASTM	A-48	CLASS 30
	CASING	CAST IRON	ASTM	A-48	CLASS 30
	IMPELLER	DUCTILE IRON	ASTM	A-536	
	CASING WEAR RING	BRONZE	ASTM	B-584-836	ALLOY 115
	MOTOR SHAFT	416 STAINLESS STEEL			
	HARDWARE	300 SERIES STAINLESS STEEL			
	"O" RINGS	NITRILE			
MECHANICAL SEALS	Standard:	UPPER AND LOWER CARBON/CERAMIC/NITRILE, TYPE 21			
	Optional:	LOWER TUNGSTEN CARBIDE/TUNGSTEN CARBIDE/NITRILE, TYPE 21			
	Optional:	LOWER SILICON CARBIDE/SILICON CARBIDE/NITRILE, TYPE 21			
UPPER BEARING	(RADIAL) SINGLE ROW — BALL				
LOWER BEARING	(THRUST) SINGLE ROW — BALL				