

MODEL: S4MRC/S4MVX — Recessed Impeller Sewage Pumps**Physical Data:**

DISCHARGE SIZE	4"
IMPELLER TYPE	BALANCED, RECESSED, 8 VANE, SEMI-OPEN VORTEX
CABLE LENGTH	35' STANDARD 50' OPTIONAL

Liquid Handling:

SOLIDS SIZE	3"
MAXIMUM LIQUID TEMP.	140°F
ACCEPTABLE PH RANGE	6 – 9
SPECIFIC GRAVITY	0.9 – 1.1
VISCOSITY	28 – 35 SSU

Temperature:

MAXIMUM STATOR	356°F
OIL FLASH POINT	390°F
HEAT SENSOR	Open: 257°F MAX./239°F MIN. Closed: 194°F MAX./119°F MIN.

Technical Data:

POWER CORD TYPE	SOOW, W	
SENSOR CORD TYPE	SOOW	
MATERIALS OF CONSTRUCTION	MOTOR HOUSING	CAST IRON ASTM A-48 CLASS 30
	CASING	CAST IRON ASTM A-48 CLASS 30
	IMPELLER	CAST IRON ASTM A-48 CLASS 30
	CASING WEAR RING	N/A
	MOTOR SHAFT	416 STAINLESS STEEL
	HARDWARE	300 SERIES STAINLESS STEEL
	"O" RINGS	NITRILE
MECHANICAL SEALS	Standard: UPPER AND LOWER CARBON/CERAMIC/NITRILE, TYPE 21 Optional: LOWER TUNGSTEN CARBIDE/TUNGSTEN CARBIDE/NITRILE, TYPE 21 Optional: LOWER SILICON CARBIDE/SILICON CARBIDE/NITRILE, TYPE 21	
UPPER BEARING	(RADIAL) SINGLE ROW – BALL	
LOWER BEARING	(THRUST) SINGLE ROW – BALL	