

MODEL: S4P(X)P - Hydromatic® Premium Efficient (HPE) Submersible Solids Handling Pumps

Physical Data:

DISCHARGE SIZE	4"
SOLIDS SIZE	2"
IMPELLER TYPE	BALANCED, ENCLOSED, 2 VANE
CABLE LENGTH	35' STANDARD WITH OPTIONAL QUICK CHANGE CONNECTOR
	50', 75', 100' OPTIONAL WITH OPTIONAL QUICK CHANGE CONNECTOR
PAINT	PAINTED AFTER ASSEMBLY. DARK GREEN, WATER REDUCIBLE ENAMEL, ONE COAT, AIR DRIED.

Temperature:

MAXIMUM LIQUID	104° F LABELED/140° F UNLABELED
MAXIMUM STATOR	356° F (180° C)
OIL FLASH POINT	309° F
HEAT SENSOR	OPEN: 275° F MAX./257° F MIN.
	CLOSED: 204° F MAX.

Technical Data:

MOTOR	PREMIUM EFFICIENT NEMA MG1, IEC 60034 -30 LEVEL IE3				
POWER CORD TYPE	W OR SOOW, WATER RESISTANT, 600V, 90° C				
SENER CORD TYPE	SOOW, 18-5, WATER RESISTANT, 600V, 90° C, 5.5 AMPS				
MATERIALS OF CONSTRUCTION	MOTOR HOUSING	CAST IRON	ASTM	A-48	CLASS 30
	CASING	CAST IRON	ASTM	A-48	CLASS 30
	IMPELLER	DUCTILE IRON	ASTM	A-536	CLASS 65
	CASING WEAR RING	BRONZE	ASTM	B-584-836	ALLOY 115
	MOTOR SHAFT	416 STAINLESSS STEEL			
	HARDWARE	300 SERIES STAINLESS STEEL			
	O-RINGS	NITRILE			
MECHANICAL SEALS	STANDARD	UPPER - SIC TYPE 2100, LOWER - SIC TYPE 2			
	OPTIONAL	CARTRIDGE SEAL			
UPPER BEARING	(RADIAL) SINGLE ROW - BALL				
LOWER BEARING	(THRUST) DOUBLE ROW, ANGULAR CONTACT - BALL				