

MODEL: S8L(X)P — Solids Handling Sewage Pumps

Physical Data:

DISCHARGE SIZE	8"
IMPELLER TYPE	BALANCED, ENCLOSED, 2 VANE
CABLE LENGTH	35' STANDARD 50' OPTIONAL

Liquid Handling:

SOLIDS SIZE	4"
MAXIMUM LIQUID TEMP.	140°F
ACCEPTABLE PH RANGE	6 - 9
SPECIFIC GRAVITY	0.9 - 1.1
VISCOSITY	28 - 35 SSU

Temperature:

MAXIMUM STATOR	311°F
OIL FLASH POINT	390°F
HEAT SENSOR	Open: 311°F MAX./293°F MIN. Closed: 243°F MAX./192°F MIN.

Technical Data:

POWER CORD TYPE	SOOW, W, GGC	
SENSOR CORD TYPE	SOOW	
MATERIALS OF CONSTRUCTION	MOTOR HOUSING	CAST IRON ASTM A-48 CLASS 30
	CASING	CAST IRON ASTM A-48 CLASS 30
	IMPELLER	DUCTILE IRON ASTM A-536
	CASING WEAR RING	BRONZE ASTM B-584-836 ALLOY 115
	MOTOR SHAFT	416 STAINLESS STEEL
	HARDWARE	300 SERIES STAINLESS STEEL
	"O" RINGS	NITRILE
MECHANICAL SEALS	Standard: UPPER AND LOWER CARBON / CERAMIC / FLUOROCARBON, TYPE 21 Optional: LOWER TUNGSTEN CARBIDE / TUNGSTEN CARBIDE / FLUOROCARBON, TYPE 21 Optional: LOWER SILICON CARBIDE / SILICON CARBIDE / FLUOROCARBON, TYPE 21	
UPPER BEARING	(RADIAL) SINGLE ROW — BALL	
LOWER BEARING	(THRUST) SINGLE ROW — BALL	