

Model: PFEV512A

Features:

General purpose pump for residential, light industrial and commercial sump or effluent applications.

- **DISCHARGE:** 2" NPT, Female, Vertical
- **LIQUID TEMPERATURE:** 77°F Continuous
- **MOTOR HOUSING/ VOLUTE:** Cast Iron, Class 30
- **SEAL PLATE:** Cast Iron, Class 30
- **IMPELLER:** Multi-Vane vortex, Cast Iron, Class 30
- **SHAFT & HARDWARE:** Stainless steel
- **PAINT:** Industrial grade powder coating
- **O-RINGS:** Buna-N
- **SEAL:** Inboard, Single mechanical, .50", Type "C", U.S. Seal, Oil Filled Chamber, Carbon/Ceramic/Buna-N with Secondary Exclusion Seal
- **UPPER BEARING:** Sleeve, oil lubricated
- **LOWER BEARING:** Single row, ball, oil lubricated
- **POWER CORD:** 20FT., SJTW, 16/3 Cord with plug, Pressure Grommet for Sealing and Strain Relief.
- **MOTOR:** Class B Insulation, Oil Filled
- **SINGLE PHASE:** Permanent Split Capacitor (PSC), Includes overload protection in motor
- **LEVEL CONTROL:** Wide angle, Mechanical, Normally Open (N/O), 16/2, SJOW cord with Piggy-Back plug. P/N: PF512040
- **WARRANTY:** 2 year

 **WARNING:** CANCER AND REPRODUCTIVE HARM-
WWW.P65WARNINGS.CA.GOV



**Submersible Effluent
2" Discharge,
3/4" Spherical Solids
Wide Angle Float**



MODEL	HP	Hz	Volts/ Ph	RPM	Full Load Amps	NEMA Start Code	Cord Size	Cord Type	Cord Length	Simplex Panel	Duplex Panel
PFEV512A	0.5	60	115/1	3450	11	H	16/3	SJTW	20Ft	n/a	n/a



Power-Flo Pumps & Systems

a Power-Flo Technologies company

877-24PUMPS • fax: 516-812-6897 • www.powerflopumps.com

Effluent Pumps - PFEV - 1/2HP - 3450RPM - 60Hz

Model: PFEV512A

Effluent Pumps - PFEV - 1/2HP - 3450RPM - 60Hz

