



Submersible Sump Pumps PW-SP Series

- Automatic submersible sump pumps
- 1-1/2" FNPT discharge
- Reinforced thermoplastic construction is corrosion and rust-resistant
- Reliable automatic operation for use in basins 14" or greater
- Tethered float switch
On/off levels:
On: 14.5"
Off: 5.5"



Model Number	Item Number	UPC	HP	Discharge	Volts	Amps	Watts	Cord	Gallons Per Hour at Height					Shut Off
									0'	5'	10'	15'	20'	
PW-SP25T	14942725	0 10121 15207 6	1/4	1-1/2" FNPT	115	2.7	300	8'	1900	1500	1200	700	-	21'
PW-SP33T	14942726	0 10121 15208 3	1/3			3.5	400		2500	2300	2100	1550	425	24'
PW-SP50T	14942727	0 10121 15209 0	1/2			4.5	500		3300	3000	2766	2244	1500	26'

Carton Specifications						
Model Number	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Master Pack Qty
PW-SP25T	7.2"	10.4"	13.8"	9	0.6	4
PW-SP33T	7.2"	10.4"	13.8"	10	0.6	4
PW-SP50T	7.2"	10.4"	13.8"	11	0.6	4

Master Pack Specifications								
Model Number	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Qty	Qty per Layer	Layers per Pallet
PW-SP25T	22"	14.75"	14.75"	36	2.77	12 Master Packs	4 Master Packs	3
PW-SP33T	22"	14.75"	14.75"	40	2.77	12 Master Packs	4 Master Packs	3
PW-SP50T	22"	14.75"	14.75"	44	2.77	12 Master Packs	4 Master Packs	3

From the manufacturers of **RED LION**