

ENGINE DRIVE CAST IRON TRANSFER PUMP

APPLICATIONS

Ideal for liquid transfer including most agricultural chemicals* and general dewatering where rugged portability is important.

FEATURES & BENEFITS

- Heavy-duty cast iron pump casing
- Durable cast iron semi-open type impeller
- Stainless steel shaft sleeve and EPDM elastomer seal
- 2" NPT suction and discharge for convenient hook-up
- Easy to prime to 25'; no additional priming required after initial fill
- Handles most liquid agricultural chemicals
- Handles up to 5/8" solid debris

*Not to be used for applying driveway sealant.

Powered by

KOHLER





Powered by Kohler® is a registered trademark of Kohler Co.

Model	Item No.	UPC	СС	Intake	Discharge	Suction Lift	Max. Head	Max. Flow (GPM)	Fuel Tank (qt)	Engine
5RLGF-8KRF	617032	0 10121 14501 6	196	2" FNPT	2" FNPT	25′	95'	170	3.8	Kohler, Air Cooled, 4 Stroke, OHV (196cc)

CARTON SPECIFICATIONS

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)		Quantity per Layer	
5RI GF-8KRF	17.5"	21"	18"	74	3.93	8	4	2

