

THERMOPLASTIC UTILITY PUMPS

APPLICATIONS

Ideal for general water transfer applications and household water removal in places like basements, aquariums, and window wells.

FEATURES & BENEFITS

- Submersible 115 Volt utility pumps
- Reinforced engineered thermoplastic construction
- Screened bottom intake design
- Removes water to within 3/16" of surface
- Includes garden hose adapter



RL-MP25

RL-MP16

Model	Item No.	UPC	HP	Amps	Volts	Discharge	Intake	Cord Length	Gallons Per Hour at Height					Shut-Off
									0'	5'	10'	15'	20'	
RL-MP16	14942731	0 10121 14154 4	1/6	2	115	1" MNPT 3/4" GHT	Screened Bottom	8'	1300	1223	1068	864	550	26'
RL-MP25	14942732	0 10121 14155 1	1/4	2.5	115	1-1/4" MNPT 3/4" GHT	Screened Bottom	8'	2200	1920	1440	900	-	22'

CARTON SPECIFICATIONS

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Quantity per Layer	Layers per Pallet
RL-MP16	6.3"	6.3"	11.75"	7.25	0.27	168	42	4
RL-MP25	6.3"	6.3"	12"	7.5	0.28	168	42	4

Thermoplastic Utility Pump

