


# EZ SERIES® IN-SITE® CL BLUETOOTH® SINGLE PHASE SIMPLEX

Data Logging Panel with Bluetooth®



Panel layout may vary with options.  
Reg. Cdn Pat. & TM Off  
C-Level™ Sensor US Patent No. 8,336,385; 8,567,242; 8,650,949

## In-Site to On-site Just Got Easier!

The EZ Series® In-Site® CL simplex control panel is designed to control one 120, 208, 240 VAC single phase pump in water and sewage installations. This innovative data logging control panel features a wireless Bluetooth® connection for your smart device, allowing safe and secure access in all weather conditions. Now there is no need to open the panel for configuration, viewing status or downloading data using the EZ InSite® Connect App.

The EZ InSite® Connect App allows you to view real time data from your smart device including pump run times, cycle counts, alarm conditions, HOA settings, power outages, tank levels, service calls and more! All system data (up to 4000 system events) can be downloaded and analyzed using our exclusive Insite Reporting software. This software formulates system data for you, creating reports quickly and easily so system conditions can be identified and corrected.

The panel utilizes the C-Level™ sensor for continuous level monitoring. It senses the level in the tank and sends a signal to the panel. C-Level™ CL40 sensor operating range is 3-39.9 inches (7.6-101.3 cm); C-Level™ CL100 sensor operating range is 3-99.5 inches (7.6-252.7 cm).

The compact redesign (10" x 8" x 4") of this panel is ideal for residential applications. The innovative internal design of components and integral mounting tabs make installation quick and simple. Includes integral padlockable latch for added safety. The panel can be converted to demand or timed dose in the field.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth® SIG, Inc. and any use of such marks by SJE Rhombus® is under license. Other trademarks and trade names are those of their respective owners. Apple and the Apple Logo are registered trademarks of Apple Inc. Google Play and the Google Play logo are trademarks of Google LLC.



## COMPONENTS

1. Enclosure base measures 10 x 8 x 4 inches (25.4 x 20.32 x 10.16 cm); NEMA 4X enclosure (ultraviolet stabilized thermoplastic with integral mounting tabs for outdoor or indoor use) includes integral locking latch as standard
2. Red LED beacon provides visual check of alarm condition
3. Circuit breaker provides pump power disconnect and branch circuit protection
4. Safety cover with touch safe design
5. C-Level™ Sensor/float connection terminal block
6. Incoming control/alarm power & pump power terminal block
7. Control Power indicator light
8. Float Status indicator lights
9. Pump Run indicator light
10. Pump manual run switch
11. Tank level indicator
12. Bluetooth® wireless module
13. Ground lug(s)
14. Auxiliary alarm Indicator

**NOT SHOWN:** Exterior Alarm Test/Silence Switch allows horn and light to be tested and horn to be silenced in an alarm condition. Alarm automatically resets once alarm condition is cleared.

Alarm Horn provides audio warning of alarm condition (83 to 85 decibel rating).

**Note:** Schematic/Wiring Diagram and Pump Specification Label are located inside the panel.

**EZ SERIES® IN-SITE® CL Bluetooth® Single Phase Simplex - Demand or timed dose, C-Level™ sensor controlled system for pump control and system monitoring with Bluetooth® wireless module.**

<b>EZI</b> CONTROL PANEL	<b>S</b> MODEL TYPE	<b>1</b> ALARM PACKAGE	<b>W</b> ENCLOSURE RATING	<b>1</b> STARTING DEVICE	<b>PUMP FULL LOAD AMPS</b>	<b>4</b> PUMP DISCONNECTS	<b>C</b> FLOAT SWITCH APPLICATION	<b>3A4A6A10E30A</b> OPTIONS (LISTED BELOW)
-----------------------------	------------------------	---------------------------	------------------------------	-----------------------------	----------------------------	------------------------------	--------------------------------------	---

<b>CONTROL PANEL</b>	✓	EZI		
<b>MODEL TYPE</b>	✓	S	Simplex (includes Options 3A4A6A10E30A as standard)	\$1,653.00
<b>ALARM PACKAGE</b>	✓	1	Alarm Package (includes test/silence switch, red light, & horn)	Base
<b>ENCLOSURE RATING</b>	✓	W	Weatherproof, NEMA 4X (engineered thermoplastic)	Base
<b>STARTING DEVICE</b>	✓	1	120/208/240V	Base
<b>PUMP FULL LOAD AMPS</b>		0	0 - 7 FLA	Base
		1	7 - 15 FLA	Base
		2	15 - 20 FLA	Base
<b>PUMP DISCONNECTS</b>	✓	4	Circuit Breaker	Base
<b>FLOAT SWITCH APPLICATION</b>	✓	C	C-Level™ Sensor (select Option 24 or 29 below)	Base

**PRICING WORKSHEET**

<b>EZI Simplex Base Price</b>	<b>\$1,653.00</b>
Alarm Package	_____
Enclosure Rating	_____
Starting Device	_____
Pump Full Load Amps	_____
Pump Disconnects	_____
Float Switch Application	_____
Total Options	_____
<b>TOTAL LIST PRICE</b>	_____

**NOTE:** Pump down applications only. Industry practices suggest that a secondary device, such as a float switch, be used for redundant activation of the high level alarm and pump shut off.

OPTIONS	DESCRIPTION	LIST PRICE
✓ 3A	Alarm Flasher (Included as standard)	\$0.00
3E	High Water Alarm Float (must also select Option 17)	\$28.00
✓ 4A	Redundant Off (Included as standard)	\$0.00
4D	Redundant Off Float (must also select Option 17)	\$28.00
✓ 6A	Auxiliary Alarm Contact, Form A (Included as standard)	\$0.00
✓ 10E	Lockable Latch - NEMA 4X (included as standard)	\$0.00
17G	SJE MilliAmpMaster™ / Pipe Clamp (per Float) - Mechanical	\$0.00
17H	SJE MilliAmpMaster™ / Externally Weighted (per Float) - Mechanical	\$7.00
24E	C-Level™ CL40 Sensor with 4' Vent Tube and 20' Cord	\$10.00
24F	C-Level™ CL40 Sensor with 4' Vent Tube and 40' Cord	\$42.00

OPTIONS	DESCRIPTION	LIST PRICE
24G	C-Level™ CL40 Sensor with 8' Vent Tube and 20' Cord	\$15.00
24H	C-Level™ CL40 Sensor with 8' Vent Tube and 40' Cord	\$47.00
24P	C-Level™ CL40 Sensor with 4' Vent Tube and 100' Cord	\$137.00
24R	C-Level™ CL40 Sensor with 8' Vent Tube and 100' Cord	\$142.00
24X	No C-Level™ CL40 Sensor	- \$307.00
29A	C-Level™ CL100 Sensor with 10' Vent Tube and 20' Cord	\$20.00
29B	C-Level™ CL100 Sensor with 10' Vent Tube and 40' Cord	\$52.00
29C	C-Level™ CL100 Sensor with 10' Vent Tube and 100' Cord	\$147.00
29X	No C-Level™ CL100 Sensor	- \$307.00
✓ 30A	Bluetooth® Wireless Module (included as standard)	\$0.00